


Top View



Side View

Front View

Note: Dimensions are nominal measurements only

SPECIFICATIONS

RECOMMENDED USE

Domestic

MATERIAL

Solid Brass

TEMPERATURE RATING

Maximum continuous working temperature 75°C
If the water temperature exceeds 75°C, an approved tempering valve must be fitted

PRESSURE RATING

Recommended minimum working pressure 150kPa
Recommended maximum working pressure 500kPa
Hot and cold water inlet pressure should be equal

SUITABLE HOT WATER UNITS

Storage tank: Yes
Continuous Flow: Yes
Gravity Feed: Not suitable

STANDARDS


WELS 5 star, 6L/min, T43741

INSTALLATION GUIDE


Note: This product must be installed by a licensed plumber. This is a general installation guide - there are many factors involved that can alter the installation method. **AU/NZ:** For installations within Australia and New Zealand, this product must be installed in compliance with AS/NZS 3500. **UK:** For installations in the United Kingdom this product must be installed in compliance with the Water Supply (Water Fittings) Regulations and Water Supply (Water Fittings) (Scotland) Byelaws. **Other:** For installations outside these countries, this product must be installed in compliance with the standards in your respective country.




- ① Mark hole in bench top at desired position and drill a 35mm hole.




- ② Remove fixing bracket and washers. Screw flexi hoses into the bottom of mixer body.




- ③ Feed flexi hoses through hole in bench and install mixer into bench



- ④ Screw fixing bracket until hand tight, do final adjustment with screw driver to lock firmly in place.



- ⑤ Connect flexi hoses to water supply. Test and commission.



*Note: Tighten aerator so that it cannot be removed by hand.

What's in the box

1 x basin mixer

1 x Rubber washer

2 x M5 screw

1 x Metal washer

1 x Locking nut


2x flexi hose



Regularly clean with mild liquid detergent or soap and water



DO NOT use cream cleaners or bleach. These substances are abrasive



DO NOT use cleaning pads with abrasive surfaces as this may scratch the material